



VICTORIA
UNIT 1/3 BUNGALEEN CRT DANDENONG
PHONE: 03 9794 5353 **FAX:** 03 9706 4353

QUEENSLAND
17 HOVEY ROAD YATALA
PHONE: 07 3382 7169 **FAX:** 07 3807 5611

EMAIL: sue@australianmesh.com.au
WEBSITE: www.australianmesh.com.au

AUSMESH 300 SAFETY ROOF MESH DATA SHEET

Everyone involved in the construction industry has an obligation to ensure building and maintenance activities are carried out as safely as possible. It begins at design stage with architects and specifiers, right through to builders and sub contractors.

Australian Mesh recommends the use of **Ausmesh 300** Safety Roof Mesh to assist in the prevention of falls during sheet laying. **Ausmesh 300** offers long term protection for workers when securely fixed to the structure over the area to be roofed and used in conjunction with appropriate edge and perimeter protection.

Ausmesh 300 Safety Roof Mesh meets the following requirements:

- Australian Standard AS/NZS 4389
- Australian Code of Practice – NSW Code of Practice 2009 – Victorian Code 2008
- Quality Assured Company to AS/ANZ ISO 9001:2009

Ausmesh 300 Safety Roof Mesh can be used on the following roofs:

- Factories
- Warehouses
- Shopping Centres
- Schools
- Hospitals/Aged Care Facilities
- Office Blocks
- Sheds

Ausmesh 300 Safety Roof Mesh features:

- Australian owned and operated company
- Australian made product (manufactured in both Melbourne and Brisbane)
- Conforms with standard AS/NZS 4389 (Safety Mesh) and HB39 (Revised copy due in 2015)
- Conforms with standard AS/NZS 4534 WO2 (Galvanised Coating Standard)
- Tested product - as required in standard (test certificate available on request)



VICTORIA
UNIT 1/3 BUNGALEEN CRT DANDENONG
PHONE: 03 9794 5353 **FAX:** 03 9706 4353

QUEENSLAND
17 HOVEY ROAD YATALA
PHONE: 07 3382 7169 **FAX:** 07 3807 5611

EMAIL: sue@australianmesh.com.au
WEBSITE: www.australianmesh.com.au

Benefits of using Ausmesh 300 Safety Roof Mesh

- Fall prevention for roof workers
- Galvanised and PVC (plastic vinyl coated product) for high corrosive areas available
- Support for insulation
- Easy to install (see our Ausmesh Red Label for installation)
- Future maintenance

Specifications:

Ausmesh 300 Galvanised Roof Safety Mesh

Width:	1800mm – 2250mm – 2400mm
Diameter:	2mm galvanised
Mesh:	300mm x 150mm
MPA:	450 – 600mpa
Coating:	To Standard AS/NZS4534:2006 WO2
Length:	Standard roll size 50 metres
Cut to Size:	Min roll size 20 metres max roll 200 metres plus
Weight:	0.48kg to 0.62kg per lineal metre
Lead time:	1 – 5 working days dependant on order size and location

Ausmesh 300 Plastic Vinyl Coated Roof Safety Mesh

Width:	1800mm only
Diameter:	2mm galvanized/zinc – high corrosive resistance
Coating:	Duravin Coating
Mesh:	300mm x 150mm
MPA:	450 – 600mpa
Coating:	To Standard AS/NZS 4534:2006 WO2
Length:	Standard Roll size 50 metres
Cut to Size:	Min roll size 20 metres max roll size 100 metres plus
Colors:	White & Black stock colors – other colors on request – may have longer than normal lead time
Lead time:	3 – 4 working weeks dependant on order size