

# Enviroseal ProctorWrap RW

## VAPOUR PERMEABLE MEMBRANE

Enviroseal<sup>TM</sup> ProctorWrap<sup>TM</sup> RW is a light duty vapour permeable wall wrap designed for use in residential timber and steel frame wall construction.

### PRODUCT DESCRIPTION

Enviroseal<sup>TM</sup> ProctorWrap<sup>TM</sup> RW is a triple layer polyolefin non-woven textile and is a highly vapour permeable wrap that allows the escape of moisture from inside the building while also acting as a barrier preventing liquid water entering from the outside. Wrapping in Enviroseal<sup>TM</sup> ProctorWrap<sup>TM</sup> RW helps minimise the risk of condensation and mould growth while improving the energy efficiency of the building.

### KEY BENEFITS

- High water resistance
- Air-tight (in combination with taping)
- Soft facings reduce flapping noise
- Non-perforated
- Light weight and easy to handle
- Also available with integrated tape (RW-IT) to improve speed of construction and provide a secure seal

### STANDARD SIZES & PACKAGING

PRODUCT NAME	WIDTH (mm)	LENGTH (m)	m <sup>2</sup> PER ROLL	WEIGHT PER ROLL	ROLLS PER PALLET	PRODUCT CODE
Enviroseal <sup>TM</sup> ProctorWrap <sup>TM</sup> RW	1500mm	30m	45m <sup>2</sup>	4.6kg	90	167641
Enviroseal <sup>TM</sup> ProctorWrap <sup>TM</sup> RW	1500mm	50m	75m <sup>2</sup>	7.9kg	35	118153
Enviroseal <sup>TM</sup> ProctorWrap <sup>TM</sup> RW-IT	1500mm	50m	75m <sup>2</sup>	7.9kg	35	165532
Enviroseal <sup>TM</sup> ProctorWrap <sup>TM</sup> RW	2750mm	25m	68.5m <sup>2</sup>	8.5kg	56	138628
Enviroseal <sup>TM</sup> ProctorWrap <sup>TM</sup> RW	3000mm	25m	75m <sup>2</sup>	9.5kg	56	155884

### ENVIROSEAL<sup>TM</sup> PROCTORWRAP<sup>TM</sup> TAPE RANGE

When required to secure, join or seal Enviroseal<sup>TM</sup> ProctorWrap<sup>TM</sup> RW it is recommended to use the following Enviroseal ProctorWrap accessory products in each of these applications.

APPLICATION	PRODUCT	WIDTH	LENGTH	ITEMS PER CARTON	PRODUCT CODE
Sealing joins	ProctorWrap <sup>TM</sup> HighTack Tape	60 mm	25m	36	155170
Sealing around penetrations	ProctorWrap <sup>TM</sup> SLS Flexi	60 mm	5m	10	117688

Highly permeable  
non perforated

# Enviroseal ProctorWrap RW

## APPLICATIONS

Enviroseal™ ProctorWrap™ RW is a highly vapour permeable, tough, light duty\* wall wrap for use as a sarking in timber and steel frame wall construction. It is tear resistant making it easy to handle during installation. In combination with taping overlaps, Enviroseal™ ProctorWrap™ RW can help form an air tight wrap for the building, reducing the loss of heated air or cooled air from the building thus improving the energy efficiency of the building envelope.

It is good practice for Enviroseal™ ProctorWrap™ RW to be separated from the exterior cladding by a cavity to allow for the drainage of any moisture that has penetrated the exterior cladding or condensation that may form on the rear face of the cladding. Adequate provision for the drainage, absorption or diffusion of moisture is required exterior to the membrane to ensure that moisture is not left trapped between the Enviroseal™ ProctorWrap™ RW and the external cladding. This is especially important for vapour tight or non-absorbent claddings such as steel.

Care should be taken when installing insulation so that this does not restrict drainage within the cavity.

## CLASSIFICATIONS

CRITERIA	REFERENCE	RESULT
DUTY CLASSIFICATION	Table 1 AS/NZS 4200.1:1994	Light*
VAPOUR PERMEABILITY	ASTM E96	4.5µg/N.s
VAPOUR RESISTANCE	ASTM E96	0.22MN.s/g
VAPOUR BARRIER CLASSIFICATION	ASTM E96	Low
EMITTANCE	AS/NZS 4201.5	Non-reflective
WATER BARRIER	AS/NZS 4201.4	High
ABSORBENCY	AS/NZS 4201.6	Unclassified
RESISTANCE TO DRY DE-LAMINATION	AS/NZ 4201.1	Pass
RESISTANCE TO WET DE-LAMINATION	AS/NZ 4201.2	Pass
SHRINKAGE	AS/NZ 4201.3	<0.5%
TENSILE STRENGTH	AS 1301.448	
• Machine Direction (k/Nm)		4.3 kN / m
• Lateral Direction (k/Nm)		2.4 kN / m
EDGE TEAR RESISTANCE	TAPPI T470	
• Machine Direction (N)		220 N
• Lateral Direction (N)		126 N
BURST STRENGTH		>200 N
FLAMMABILITY INDEX	AS/NZ 1530 Part 2	≤ 5
Allowable UV exposure prior to completion of cladding		4 weeks

\*Enviroseal™ ProctorWrap™ RW is classified as light duty in accordance with the value specified for bursting strength and therefore does not meet the deemed-to-satisfy provisions for use in roof applications.

## DURABILITY

Although Enviroseal™ ProctorWrap™ RW can be used as temporary protection during construction, it can not be used as a primary waterproofing membrane. The product may be damaged by careless handling, high winds or vandalism, and should not be left uncovered for longer than is absolutely necessary. Any damaged areas should be replaced before completion.

Ensure that Enviroseal™ ProctorWrap™ RW is covered up by the primary cladding as soon as possible, and not left exposed to UV for longer than 4 weeks. Enviroseal™ ProctorWrap™ RW is not to be used in open joint rain screen cladding installations where it could be exposed to long term UV radiation. For advice on such applications where Enviroseal™ ProctorWrap™ Black Label may be suitable please contact CSR Bradford Australia.

## SAMPLE SPECIFICATION

Sarking should be CSR Bradford Enviroseal™ ProctorWrap™ RW vapour permeable membrane, tested to AS/NZS 4200.1, secured directly to the outside of the wall frame at maximum 300mm spacing and in accordance with product user guide. Breather foil does not comply with this specification.



CSR Bradford  
Locked Bag 1345 North Ryde BC NSW 1670  
[csrbradford.com.au](http://csrbradford.com.au)  
Email: [bradfordenquiries@csr.com.au](mailto:bradfordenquiries@csr.com.au)

For further information  
call **1300 850 305** or  
visit [bradfordinsulation.com.au](http://bradfordinsulation.com.au)



CSR Bradford is a business division of CSR Building Products Limited ABN 55 008 631 356

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Bradford website for the latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application.